

Technical drawing of a rectangular plate with the following dimensions and features:

- Overall width: 1997
- Overall height: 2200
- Three vertical sections with widths: 665.5, 666, and 665.5.
- A hole with diameter $\varnothing 75$ is located in the rightmost section.
- The hole is positioned 700 units from the bottom edge.
- The hole is positioned 497 units from the left edge of the rightmost section.
- The distance between the center of the hole and the next vertical section to the left is 1000 units.
- The distance from the center of the hole to the right edge of the plate is 500 units.

Technical drawing of a rectangular plate with dimensions and labels:

- Top edge:** A dimension of 70 is indicated at the top right corner.
- Left edge:** A label "連結用インサート M12" (Insert for connection M12) with an arrow pointing to the top-left corner.
- Bottom edge:** Dimensions are indicated at the bottom: 500 (left section), 1000 (middle section), and 497 (right section).
- Right edge:** A vertical dimension of 1000 is indicated on the right side.
- Internal features:** Two vertical lines with circles at the top represent holes or inserts, positioned at the boundaries of the 500 and 1000 bottom dimensions.

Technical drawing of a square plate. The overall dimensions are 1440 (width) and 1997 (height). The plate features a central vertical slot with a width of 10, indicated by two dimension lines labeled "C10". A detail view is shown in the bottom right corner, labeled "放大图" (Magnified View). This detail view is a circular cross-section showing a 90° angle and a 15° angle, with a dimension of 15 indicated for the radius of the corner.

Technical drawing of a corner detail. The drawing shows a corner with a radius of R100. Dimensions include a horizontal offset of 81, a vertical offset of 411, a vertical distance of 1605, a horizontal distance of 1250, and a radius of R100. A dimension of 558 is shown for a horizontal offset on the right side. A dimension of 67 is shown for a vertical offset on the right side.

558



1907

製品名	KCウォール II 型
サイズ	2200×2000
参考重量	2626 kg
栗本建材株式会社 クリモトコンクリート	